

Multi-lens Multi-screen Indoor camera



- 1. 6MP HD indoor PTZ camera;
- 2. Three-lens three-screen, 360-degree surveillance;
- 3. Dual light source design, built-in infrared light + white light, night vision infrared and night vision full color can be set;
- 4. Pan&Tilt: horizontal 0~355 degrees, vertical 0~90 degrees;
- 5. The other two cameras support manual adjustment of 240 $^{\circ}$ horizontal and 180 $^{\circ}$ vertical
- 6. WIFI (IEEE 802.11b/g/n) 2.4GHz;
- 7. Support TF storage and cloud storage;
- 8. Two-way voice intercom, three-way video synchronous recording and playback;
- 9. Support motion detection, intelligent alarm;
- 10. Support automatic tracking;
- 11. Support Android/IOS APP remote management;
- 12. power supply DC 5V.

Model	LS-WA15	
	SOC	T31
	Sensor	1/3" CMOS
	Minimum illuminance	5Lux @(F1.4,AGC ON) ,0 Lux with IR;
	Shutter	Shutter adaptation
	Lens	4mm + 4mm +4mm three lens
	PTZ	Horizontal 0 ° - 355 °, vertical 0 ° - 100 °
	Lens interface type	M12
	Day night conversion mode	Automatic, ICR infrared filter
	Infrared irradiation distance	30m (depending on the environment)
	Digital noise reduction	2D / 3D digital noise reduction
	Wide dynamic range	Digital wide dynamic
	Video compression rate	Rate adaptation
	Audio compression standard	G.711a

LS VISION: For a Better World! _____ www.lsvisionhd.com





	I	
	Audio compression rate	Rate adaptation
	Audio operating mode	Simplex bidirectional
	Audio and video cloud storage	Three channel 2MP synchronous storage, synchronous look back;
	Audio and video local storage	Micro SD, Three channel 2MP synchronous storage, synchronous look back;
	Real-time Preview	Three-screen, Three channel 2MP synchronous preview;
Image	Image size	HD:2MP SD:640x360
	Frame rate	15 frames (day) / 12 frames (night)
	Image settings	Mirror / Flip
	Backlight compensation	support
Network function	Intelligent	Motion detection/automatic tracking
	One click configuration	Code scanning addition, hotspot AP configuration, manual addition
	Interface protocol	Cloud private protocol
	General function	Dual code stream, image, password protection
Interface	Storage interface	Micro SD card (up to 128G) or cloud storage
	Power interface	Φ 5.5 round head power interface
	Reset interface	Support tail line key reset (optional)
	Wired network port	/
Wireless parameters	Wireless standard	802.11b/g/n
	Radio frequency	2.4 GHz
	Channel bandwidth	Support 20MHz
Cloud services	Cloud services	Deng Hong video cloud
	APP	FFvideo (download from App Store)
	cloud storage	Deng Hong video cloud
General specifications	Operating temperature and humidity	-10℃~50℃, 10%~90 (RH)
	Power supply	DC12V±10%
	Power waste	5W Max without night vision
	Color box	
	PCS/CTN	
		-