

LS-PC101

2MP starlight Intelligent people counting dome camera



Key features:

- Support human detect,real time counting entrance /exit /stay people quantity
- Support set security people quantity,camera will alarm when overcrowded;
- starlight camera is able to deliver high resolution color image even in low light environment reaching 0.001lux(color) or 0lux(B/W)and near infrared light environments without any compensation light
- Built-in auto focus motor lens,easy to adjust video image.
- Built-in smart Infrared light,low consumption,auto to switch color &B/W model

Model:		LS-PC101
Image Sensor		1/2.8" Progressive Scan CMOS
Shutter Time		1/12s~1/8000s
Min. Illumination		Color 0.005Lux@F1.2; B/W 0.007Lux@F1.2;
S/N		≥50dB(AGC OFF)
WDR		≥80dB
Noise Reduction		3D Digital Noise Reduction
AF Lens		2.8-12mm F1.4, Horizontal view: 43°~14
Video Compression		
Video Compression		H.265+/H.265/H.264/MJPEG
Code Type		Main Profile
Video Bit Rate		32 Kbps~16Mbps
Video Image		
Image setting		Brightness/Contrast/Saturation/Sharpness/AWB/AGC; Support privacy masking and OSD
Video resolution		1920 × 1080
Video resolution	Main stream	1080P(1920×1080)/1280×720
	Sub stream	D1(704×576)/VGA(640×480)/640×352/QVGA(320×240)
Video frame		50Hz: 1~25fps 60Hz: 1~30fps
On-screen display(OSD)		Support
Smart Function		
Smart code		Support low bit rate、low latency、enhanced coding of ROI area, up to 4 ROI area
Smart detect		Motion detect

Smart control	Support smart control alarm open、alarm shut、fault clear、smart noise reduction
AI Function	
Human Detect	Support Human detect
People counting	Real time to counting people quantity
People gather alarm	Support set security gather quantity,camera will alarm when overcrowded
Mask detect	/
Network	
Network protocol	IPv4,TCP/IP, UDP, RTP, RTCP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP;
Access standard	ONVIF/ GB28181
User number	Max 8 user at same time
Connect Interface	
Network Interface	1CH RJ45 10M/100M
Audio Interface	1CH Audio out,can connect loudspeaker 1CH Audio In
Alarm out Interface	1CH alarm out ,can use to connect alarm device
Reset Interface	1CH Reset
General Parameters	
IR Distance	Max up to 30M
Power supply	DC 12V±20% / POE(802.3at) (Optional)
Power consumption	DC12V: 12W MAX
Working Temperature&humidity	-30℃~60℃,humidity lower than 95%(No condensation)
Waterproof	IP66
Device Dimensions	φ 142. 4*112. 6mm
Net weight	1500g ((include install parts))
Install way	Wall or hoisting

Dimensions(mm):

