

LS VISION 5MP IP Camera LS-NB12503V

Features:

- ❖ 1/2.8" Sony CMOS sensor
- ❖ Full HD resolution 2592*1944
- ❖ Ultra low illumination 0.01Lux
- ❖ Day/Night (ICR), AWB, 2D/3D-DNR, IR-CUT
- ❖ D-WDR, Motion Detection, Privacy Mask, Mirror, rotate
- ❖ RTSP and Onvif compatible
- ❖ H.265/H.264 dual-stream media server
- ❖ Easy-to-use P2P Cloud service
- ❖ Multiply web browser, PC Client, mobile APP remote access
- ❖ Optional customization Lens/Audio, etc.
- ❖ Lightning protection 4000V
- ❖ Strong water-proof housing, IP66
- ❖ Support POE 48V



Technical Specifications:

Model	LS-NB12503V
Camera	
Image Sensor	1/2.8" OS05A10
Effective Pixels	2592(H)×1944 (V)
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto
AGC/BLC	Support
DNR	2D/3D DNR
Other	Multi-lines OSD, Motion Detection, Privacy Mask, Mirror, Rotate
Encode	
Embedded Solution	MSC316DM
Video Standard	H.265/H.264
Video Resolution	Main stream: 2592×1944@15fps/2560×1440@25fps/2048×1520@25fps/ 1080P/720P@30fps Sub stream: D1/VGA/360P@30fps, etc.
Video Bitrates	32Kbps - 6Mbps, VBR/CBR

Audio Standard	G711U/G711A/ACC, optional
IR Led	
IR Led	24pcs Leds
IR Distance	30M
Lens	
Focal length	2.7-13.5mm motorized lens
Optional Function	
Audio,etc.	
Network Services	
Protocol	HTTP/RTSP/RTMP/DHCP/NTP/ONVIF/P2P/UPNP/GB28181, etc.
P2P	Yes
Web	IE , Firefox, etc.
Media	CMS, Android, IOS
ONVIF	2.6 compatible
General	
Network Port	1-RJ45, 100Mbps, POE optional
Power Supply	Support POE 48V &12 VDC ± 10%
Power Consumption	< 9W
Operating Temp.	-30°C-(+60)°C, 10%-90%RH

*This statement is subject to change witho ut notice