


## LS-NB12201V HD H.265 1080P IP Camera



### Features:

- ❖ 1/2.8" CMOS sensor
- ❖ HD resolution 1920\*1080P
- ❖ Low bit stream, Increase storage time
- ❖ Motion Detection, Privacy Mask, Mirror
- ❖ RTSP and Onvif 2.6 compatible
- ❖ H.265/H.264 dual-stream media server
- ❖ Easy-to-use P2P Cloud service
- ❖ Multi web browser, PC Client, mobile APP remote access
- ❖ Lightning protection 4000V
- ❖ Strong water-proof housing, IP66
- ❖ 24 pcs IR Leds, IR distance 30 meters
- ❖ 2.7-13.5mm varifocal Lens
- ❖ Support POE 48V

### Technical Specifications:

|                   |                                                                                                                                             |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Model             | LS-NB12201V                                                                                                                                 |
| Camera            |                                                                                                                                             |
| Image Sensor      | 1/2.8" IMX307 CMOS                                                                                                                          |
| Effective Pixels  | 1920(H)×1080 (V)                                                                                                                            |
| Image Quality     | Brightness setting, Saturation setting, Sharpness setting, Contrast setting, Backlight compensation setting, Strong light suppression, etc. |
| Min. Illumination | 0.01Lux@F1.2(AGC ON)                                                                                                                        |
| Day/Night         | Auto/Color/(B/W)/Timing                                                                                                                     |
| White Balance     | Auto/Indoor/Outdoor                                                                                                                         |
| DNR               | 2D/3D DNR                                                                                                                                   |
| Other             | Motion Detection, Privacy Mask, Mirror, Flip                                                                                                |
| Encode            |                                                                                                                                             |
| Embedded Solution | SSC325                                                                                                                                      |
| Video Standard    | H.265/H.264 Double code                                                                                                                     |
| Video Resolution  | Main stream: 1080P@25fps / 720P/D1@30fps<br>Sub stream: 360P/CIF@30fps                                                                      |
| Video Bitrates    | 500Kbps -4Mbps, VBR/CBR                                                                                                                     |

|                          |                                   |
|--------------------------|-----------------------------------|
| Audio Standard           | G.711-u                           |
| <b>IR Led</b>            |                                   |
| IR Led                   | 24 pcs IR Leds                    |
| IR Distance              | 30M                               |
| <b>Lens</b>              |                                   |
| Focal length             | 2.7-13.5mm varifocal Lens         |
| Zoom                     | 4X                                |
| <b>Optional Function</b> |                                   |
| Audio, etc.              |                                   |
| <b>Network Services</b>  |                                   |
| Protocol                 | RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP |
| P2P                      | Yes                               |
| Web                      | IE , Firefox, etc.                |
| Media                    | CMS, Android, IOS                 |
| ONVIF                    | 2.6 compatible                    |
| <b>General</b>           |                                   |
| Network Port             | 1-RJ45, 100Mbps                   |
| Power Supply             | Support POE 48V& 12 VDC ± 10%     |
| Power Consumption        | < 7 W                             |
| Operating Temp.          | -30℃-(+60)℃, 10%-90%RH            |

\*This statement is subject to change witho ut notice